



Pipe Extrusion Outputs, techn. data's

Output rates, depends on material, formula, application

□ PVC-Pipe / CPVC-Pipe / PVC-Foam Core Pipe / Multi-layers Pipe

□ Output Range - Conical Twin Screws:

- TGI-Konex38 120 kg/h
- TGI-Konex50 230 kg/h
- TGI-Konex63 350 kg/h
- TGI-Konex72 550 kg/h
- TGI-C50 180 kg/h
- TGI-C60 300 kg/h

□ Output Range - Parallel Twin Screws (also with different LD available):

- TGI-P75-26D 420 kg/h
- TGI-P75-36D 500 kg/h
- TGI-P90-26D 650 kg/h
- TGI-P90-36D 700 kg/h
- TGI-P114-26D 900 kg/h
- TGI-P114-36D 1050 kg/h
- TGI-P130-26D 1200 kg/h

□ Output Range – Single Screws (also with different LD available):

- TGI-SS20-Coex PE/PP-Pipe = 4 kg/h
- TGI-SS30-Coex PE/PP-Pipe = 15 kg/h
- TGI-SS40-Coex PE/PP-Pipe = 25 kg/h
- TGI-SS45-36 PE/PP-Pipe = 280 kg/h
- TGI-SS60-36 PE/PP-Pipe = 450 kg/h
- TGI-SS75-36 PE/PP-Pipe = 700 kg/h
- TGI-SS90-36 PE/PP-Pipe = 900 kg/h
- TGI-SS125-36 PE/PP-Pipe = 1300 kg/h
- TGI-SS150-36 PE/PP-Pipe = 1700 kg/h

□ Pipe production line Downstream:

- TGI-PDH □ Pipe die heads for different applications and materials
- TGI-VCT □ Vacuum Tanks + Calibration sleeves
- TGI-SPT □ Spray Tanks
- TGI-HOU □ Haul off units, with 2 chains, or multiple chains
- TGI-CTU □ Cutting units, saw cutter, planetary cutter (chip less cutter available)
- TGI-SDT □ Sliding tables



PIPES

Dallan TGI Globe Extrusion Technology Co., Ltd

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION

X-TRUSION